

A METHOD AND APPARATUS FOR CALIBRATING A CAMERA

5

BACKGROUND OF THE INVENTION

The invention relates to camera lens systems having optical characteristics (such as zoom and focus) that can be modified while the camera is in use; the lens system is for mounting on a camera that is "instrumented", i.e. having its own sensors for delivering signals representative of the angular position of the camera relative to its stand. A particularly important, although not exclusive, application of the invention lies in lens systems for use with cameras that are incorporated in installations that are capable of replacing the representation of a target zone in the image supplied by the camera and occupying a fixed position in the space viewed by the camera with a stored "model" or pattern that can be still or animated, and with the model being scaled appropriately. The position and the area of the fixed zone are stored in the installation which includes computation means and image synthesis means capable of computing the deformation or "warping" that need be imparted to the model, and capable of superimposing the warped model.

In general, the sensors used are digital encoders having the advantage of suffering no drift and of delivering an output that is directly usable by data processing equipment.

Installations of the above type already exist. To obtain satisfactory precision, implementation of such installations requires a lengthy and arduous calibration stage to be performed on site prior to shooting, during which a camera operator aims successively at various different portions of the entire space that can be scanned while using different degrees of zoom and a plurality of different focus settings, and the various sensors are calibrated from the shots using close and far fixed characteristic points in the observed scene as references. Those methods restrict the field of operation.

Other parameter measurement systems are known and for instance reference may be made to the paper "A high precision

camera operation parameter measurement system and its application to image motion inferring " by Zheng et al, in "Proceedings of International Conference on Image processing, ICIP '99, Kobe, Japan, to which reference may be made.

5

SUMMARY OF THE INVENTION

The inventors have become aware that some of the transfer functions and characteristics to be identified are intrinsic to the lens system itself, whereas others depend on the interface between the lens system and the camera and can be referred as being "extrinsic". In particular, a given lens will not always be in exactly the same position relative to the camera's focal plane that is occupied by the array of photosensitive sites, due to inevitable tolerance (wear), assembly conditions, and image standards.

On the basis of these observations, it is an object of the invention to simplify quite considerably the operations that need to be performed on site each time a new camera or a new location is used.

To do this, the invention provides in particular a calibration method comprising the steps of :

- calibrating, once for all, intrinsic characteristics or parameters of the lens system and establishing a computer file containing said characteristics; and

- on site, calibrating the assembled camera and lens system so as to define transfer functions between signals coming from camera orientation sensors and lens system sensors and real characteristics on the basis of said file and of signals obtained by shooting characteristic points of the scene to be observed.

In another aspect, a calibration method is proposed enabling a correspondence table to be determined between at least the output signals from zoom and focusing sensors Z and F placed on a camera lens and constituted by digital coders with real values for focal length and geometrical deformation, the method comprising:

- (a) a step, that is performed once for all, of determining the intrinsic characteristics of the lens; and

(b) a step, that is performed on site after the lens has been mounted on a camera for a particular purpose, of resetting origins.

This greatly simplifies on-site operations since they can be reduced to taking a few shots that can be performed in a few minutes by an operator who has been trained but is not a specialist, with all of the intrinsic characteristics of the lens system being already available. The lens system calibration file need merely be selected, the constants of the system (type of camera head, position of camera on camera head) be given, and then the necessary shots be taken. In addition, this method provides great accuracy since intrinsic calibration is performed free from operating constraints.

The invention also proposes an assembly or package that can be used for use of a camera lens which constitutes said lens system, the assembly comprising the lens itself plus a file (ROM file, flash memory, disk) accompanying it and loadable into a computer used during the on-site portion of calibration.

The invention also provides software that can be executed on a computer and that includes a database containing the intrinsic characteristics of a lens system and a program responsive to the database and to measurements performed on site while the lens system is mounted on a camera to determine the extrinsic characteristics and the complete two-dimensional (2D) transfer function between the scene as seen by the camera and the displayed image.

In another aspect of the invention, there is provided a calibration method enabling a correspondence table to be established between at least the output signals from zoom and focus sensors Z and F placed on a camera lens and constituted by digital coders, and real values of focal length and geometrical deformation for the camera on which the lens system is mounted, the method comprising:

(a) a stage ,performed once and for always, of determining the intrinsic characteristics of the lens, which stage is performed after the lens has been mounted on a camera, and during which the following steps are performed:

- taking a plurality of shots with the camera in different pan and tilt orientations and different zoom and focus values (where focus influences focal length);

- for each shot, reading output signals from the coders and the positions in the image of at least two points, a near point and a far point, in the scene observed in the shot; and

- drawing up an intrinsic calibration table by comparing the signal values and the positions of the points in the image provided by the camera; and

(b) a stage performed on site after the lens has been mounted on a camera that is to be used on site, during which stage, the following steps are performed:

- specifying operating conditions (for example: PAL, NTSC, ..., standard; 4/3 or 16/9 image ratio, high definition, ... image size; camera position on the camera head after balancing, etc.); and

- repeating only some of the operations performed in stage (a), solely insofar as they are necessary for resetting origins and for determining parameters including the pixel aspect ratio.

The near point observed during stage (a) could be provided by a point source such as a light emitting diode (LED) or a laser diode placed at a distance that is slightly greater than the nearest focus distance. The far point must simulate viewing at infinity and is preferably at least 100 meters (m) away.

In general, all of the measurements in stage (a) should be performed prior to performing the computations which are subsequently performed globally either on site or remotely. For example, these measurements can be performed using a program that is well defined as a plurality of steps, each step being performed with the same zoom setting, and a plurality of different focus settings.

The independence between the zoom and focus characteristics then makes it possible to represent the lens by a mathematical model in the form of two tables representing two families of functions each having a single input variable,

whereas an approach without separation would have required a table with two input variables which would make interpretation difficult. In other words, the lens is represented by a mathematical model using single input variable functions only.

5 An additional advantage of the method is that it makes remote calibration possible so there is no need to disclose the calibration software, and that would be impossible without the last two steps of stage (a) being separated. An application server can be provided using the SMTP protocol, while the calibration machine is connected temporarily to the Internet. For the purposes of an Internet connection, the data obtained by the "snaps" mentioned below are sent to a server which responds by sending a calibration file which can optionally be encrypted.

15 The camera fitted with the lens can be associated with at least one gyrosensor (gyro or rate gyro) which provides angle measurements in addition to those supplied by the camera head sensors, e.g. when the camera head is subjected to vibration (as in a stadium). The gyro is for measuring tilt for which out-of-balance weight can give rise to measurement errors. 20 The camera is balanced statically but not dynamically: so long as it is not in motion, it is balanced, but under the effect of excitation (for the most part along the vertical axis if the structure is sound) translation motion gives rise to tilt rotation. On a structure having resonant modes that are more troublesome, for example horizontal translation motion, it is possible to envisage a second gyrosensor responsive to pan. 25

30 The data originating from the sensors representing the state of the instrumented camera can be used directly in conventional manner or can be converted into an audio frequency signal, thereby making it possible to use the ordinary audio-visual environment for data transport and/or recording.

35 The above characteristics and others will appear more clearly on reading the following description of a particular embodiment given by way of non-limiting example. The description refers to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

- Figure 1 is a diagram showing the functions of the various sensors carried by the lens and the head of an instrumented camera intended for enabling a target zone to be substituted;

- Figure 2 shows a common way of mounting a camera head, in which tilting movements are added to pan movement (in contrast to a so-called "equatorial" mount);

- Figures 3A and 3B show types of deformation that occur when an image is formed;

- Figure 4 shows locations in which the same scene reference point is placed for initial intrinsic calibration and subsequently for extrinsic calibration; and

- Figure 5 is a simplified summary chart showing one possible way in which the mathematical model can be implemented.

DETAILED DESCRIPTION OF THE INVENTION

The camera shown diagrammatically in Figure 1 comprises a stand 10 on which a head support 12 can turn about a pan axis 14. The head 16 can turn relative to the support 12 about a tilt axis 18. On the camera head there is mounted a lens 20 which generally carries a focusing ring 22 and a zoom ring 24. These two rings are provided with respective absolute angle encoders of high resolution. The tilt angle ϕ relative to the support is provided by a sensor 26. The angle θ about the pan axis is supplied by a sensor 30. All of these sensors are connected to acquisition electronics 32 which converts the data from the sensors into the form of a serial signal (RS232, RS422) or into audio modulation.

In order to ensure that inlaying can be performed precisely, it is necessary to use the signals from the sensors to determine exactly where the target zone for replacement is to be found in the image, which zone remains motionless within the scene, and it is necessary to do so regardless of camera zoom, focus, or orientation. Unfortunately, image transformations when these parameters are combined are far

from being simple homothetic transforms, and they are far from being the same for all lenses of a same type.

Calibration is a deterministic process, thus making it possible to store the behavior of the lens for all zoom and focus positions.

The following are described below in succession:

- intrinsic calibration: this generates a file containing the intrinsic geometrical characteristics of the lens; the lens is then entered into a database of calibrated lenses; calibration needs to be done for each lens, even for lenses of the same model and from the same manufacturer, but on each lens it need be done only once and for always; and

- extrinsic calibration known as lens camera setting (LCS): it takes account of operating constraints associated with the lens being mounted and dismounted on a particular camera giving rise to alignment differences which occur with a single camera and with different cameras (image format). LCS needs to be performed each time a lens is mounted on a camera, even if the same lens is newly mounted on the same camera (mechanical tolerances).

Once operations have been performed, the behavior of the camera used for shooting will have been stored for an entire series of values delivered by the zoom sensor Z and the focus sensor F, thus making interpolation possible.

Intrinsic calibration, transposable from one camera to another

The lens is modelled by defining a plurality of parameters that vary as a function of its focal length f at least:

- absolute focal length for two known distance values of the target points, one being at infinity P1 and the other point, P2, being nearby (in the range 5 m to 15 m, depending on the type of lens);

- a coefficient K representing geometrical deformation in the radial direction; and

- a focal length correction associated with the focus setting;

and global parameters that are independent of zoom:

- position of the eye;
 - aspect ratio (pixel height/width ratio in the matrix of light sensitive sites); and
 - tilt while taking a horizontal shot because the tilt
- 5 coder does not give a zero value under such circumstances.

The position of the eye is a point on the optical axis such that if it is caused to coincide with the vertical or pan axis, then no parallax is visible in the image when panning between a near point (e.g. as implemented on a pane of glass)

10 and a point at infinity.

Initialization, wide angle and narrow angle

The operation begins by entering the identity of the lens into memory .

15 P1 and P2 are selected points;

F1 and F2 are focus values at full zoom Z_n (maximum magnification or zoom in) selected for P1 and P2;

F3 is a focus value selected arbitrarily between 1.1 F2 and the value of F at the nearest focus distance, $Z_1, \dots, Z_i, \dots, Z_n$ being reference zoom values;

20

T, B, L, R, C, TL, BR, TR, BL being the nine positions that a given point is caused to occupy in the image by manipulating the camera (Figure 4),

the operator begins by performing six initialization operations. During each such operation, referred to as a "snap", the operator moves the camera so as to bring the point under observation into one of the nine above-mentioned positions, and clicks on the point. On each occasion, the values supplied by the coders and the distance between the

25

30 points in the scene and the camera are stored:

P1, F1, Z_n , C

P1, F1, Z_1 , C

P1, F1, Z_1 , L

P1, F1, Z_1 , R

35 P2, F2, Z_n , C

P1, F1, Z_1 , B

No computation is performed at the end of this stage; the operator then moves onto measurements at wide angle (zoom out) Z1 and narrow angle (zoom in) Zn.

5 Wide and narrow angles, corresponding to different focal lengths, with focusing F1, F2, and F3

The operator takes five snaps to define the wide angle condition:

10 P1, F1, Z1, T
P1, F1, Z1, TL
P2, F1, Z1, T
P2, F2, Z1, T
P2, F3, Z1, T

and then five snaps in narrow angle:

15 P1, F1, Zn, H
P1, F1, Zn, TL
P2, F1, Zn, T
P2, F2, Zn, T
P2, F3, Zn, T

20 At the end of this stage, the software runs a first series of computations, initially giving default values to global parameters:

DO

{DETERMINE Z1 ZOOM PARAMETERS FROM THE 5 Z1 SNAPS
DETERMINE Zn ZOOM PARAMETERS FROM THE 5 Zn SNAPS
DETERMINE GLOBAL PARAMETERS FROM THE 6 D SNAPS
INITIALIZATION}

UNTIL CONVERGENCE

30 If there is no convergence, the software is designed to ask the operator to verify the snaps or to do them again.

The results of all the above snaps and of the following snaps are stored in the computer memory in order to enable the operator to return to the position of some particular point, if the operator so desires.

35 By way of example, a "snap" can cause a 200 pixel × 150 pixel window to be scanned in the full image, corresponding to about 60 k.

Intermediate zooms

Measurements are performed at various intermediate amounts of zoom Z_2, Z_3, \dots, Z_{n-1} . For each reference zoom, the operator takes five more snaps:

5 P_1, F_1, Z_i, T
 P_1, F_1, Z_i, TL
 P_2, F_1, Z_i, T
 P_2, F_2, Z_i, T
 P_2, F_3, Z_i, T

10 At the end of this step, the software computes zoom-related parameters for each of the values Z_i . The software is designed to ask the operator to verify the snaps or to start again if convergence does not occur.

15 The most important point is focal length which varies as a function of zoom, and to a lesser extent focus. Focal length makes it possible to conserve a relationship between image points and coordinates in three-dimensional (3D) space.

Each computation step makes it possible to define a parameter of the lens by a sequence in which:

- only previous parameters are necessary;
- parameters that are still unknown do not vary.

These steps comprise in succession:

- 1) determining the optical center of coordinates (C_x, C_y) on the matrix due to the offset \underline{e} ;
- 2) aspect ratio = $Y_{\text{pixel}}/X_{\text{pixel}}$ for the reference camera;
- 3) absolute focal length, which is a function of zoom for constant focus;
- 4) focus correction having the form $1 + \varepsilon(\text{Focus})$ where $\varepsilon(\text{Focus}) = A \times \text{Focus}^2 + B \times \text{Focus} + C$; and
- 30 5) the radial distortion coefficient K that is involved in a formula of the form $r' = r + Kr^3$;

where \underline{r} is the distance to the optical center and K is a function solely of the focal length, and is positive for barrel deformation and negative for pin-cushion deformation.

35 A distinction is made between:

- constant parameters
 - position of the optical center
 - aspect ratio or "pixel ratio"

- absolute focal length scale; and
- parameters that are a function of zoom
 - focal length
 - K
- 5 - focus connection
- eye position.

In order, the following are determined:

- the fixed parameters;
- curves of:
 - 10 - focal length (zoom) at constant focus;
 - K (of focal length) at constant focus;
 - eye position (focal length) at constant focus; and
 - focus correction (focal length).

15 The analytical expressions found experimentally are piece-wise logarithmic for zoom over each range between two values Z_i and they are polynomials of order 2 for focus correction. They are stored in the form of particular values for parameters in a mathematical model.

20 Once intrinsic calibration has been performed, the results of the processing performed locally or on a remote server are stored in the form of a file in a read-only memory (ROM) or in a flash memory, or on a hard disk.

25 A file is then available which contains calibration parameters that are as close as possible to the real characteristics of the lens.

Extrinsic calibration

30 When the lens is mounted on a camera other than the reference camera on which its intrinsic characteristics were determined, there will be a small change in optical center, and this gives rise to errors. Camera balancing moves the "eye position" and gives rise to a parallax effect (camera rotation gives rise to a small amount of movement in translation of unknown sign) which is most troublesome when

35 the object is close. Finally, the image sensor can be of geometry and size that are different depending on image standard.

Extrinsic calibration, which can also be referred to as lens camera setting or LCS, amounts to adjusting calibration data. It does no more than recompute constant parameters associated with camera initialization, and including
 5 parameters that come from two sources:

- lens-camera coupling:

- optical center (Cx, Cy);
- pixel ratio ($Y_{\text{pixel}}/X_{\text{pixel}}$ = pixel aspect ratio);
- focal length scale adjustment (absolute focal

10 length);

- base plate offset adjustment (basis for eye position); and

- adjustment of absolute focal length scale;

- possibly also camera-head coupling (with multiple
 15 origins for each parameter):

- roll: the horizontal axis of the matrix is at an angle with the tilt axis, adjustment of the offset of the camera baseplate on the stand; and

- tilt zero: the value given by the tilt encoder when
 20 the optical axis is exactly orthogonal to the pan axis.

This list is not limiting, and other parameters could be incorporated:

- pan zero (optical axis not exactly parallel to tilt axis);

- focus zero (end stop unreliable on some lenses); and

- zoom zero (end stop unreliable on some lenses).

In order to be able to provide the computer associated with the camera and a subsequent system for inserting a virtual model in the position of a target with elements
 30 enabling them to identify the exact location in the image where an insertion is to be performed, the on-site operator performs above operations 1 and 2 to identify the optical center and the aspect ratio and also to determine the absolute focal length. The computer containing the program associated
 35 with the lens resets the constant parameters as supplied by the file associated with the lens. A mathematical model is thus obtained that is of the kind shown in Figure 5. In other words, the information provided by the sensors is corrected so

as to enable the exact position of the target in the image as reproduced, thus enabling the target to be replaced by the model after the model has been scaled appropriately (and possibly also deformed due to perspective or to geometrical
5 aberrations of the lens), or the model can be added to the target, in semitransparent form, after it has been scaled.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
22